

# APRSlink Commands

update 2020-06-30

<b>WLNK-1</b>	<b>COMMENT</b> text part of the APRS station to be stated for automatic info message from the server that Winlink messages are available! Plus it is the <b>CALLSIGN</b> to forward the available queries to.
<b>H or ?</b>	Return brief Help. Help is also returned whenever APRSlink does not understand a command. Use "?" followed by a command letter for detailed help for that command. Example: "?L" for help with the List command.
<b>L</b>	Return a List of pending messages (a maximum of 5 are returned). The List command queries the Winlink e-mail server and builds a list of up to 5 recent messages. Other commands operate on this list of messages using the message number (#).
<b>R#</b>	Read message number # (# is one of the numbered messages returned via the List command). Example: "R2"
<b>Y#</b>	reply to message. Reply to message number # (# is one of the numbered messages returned via the List command). Example: "Y2"
<b>SP</b>	This simplifies the sending of messages from APRS devices considerably. Here's the format: SP <email address – or- callsign –or- alias> <subject> Then, anything you send to WLNK-1 other than /EX or the (P)layback command makes up the body of your message. If you mess up and need to start over, just issue a new SP command.  Example (all sent to WLNK-1):  SP sam@iam.com Header Test Message  Some text for the body of the message.  Some more text for the message.  /EX  Each line is a separate APRS message, but the need for entering specific commands for each line/message has been removed. You type and send as much text as necessary and then send /EX as a separate APRS message to complete your email.
<b>/EX</b>	Complete and send the composed message. You should receive a confirmation message.
<b>P</b>	Playback message. Play back message lines for the message being written.
<b>SMS</b>	Send short message (one line). Syntax: SMS <email address, callsign, or alias> <message> Example: SMS sam@iam.com A short message to Sam
<b>A AL</b>	Create/update an alias for an e-mail address.  Example: A sam=sammy.miller@somealongdomainname.net  Then use "SP sam" instead of "W sam@somealongdomainname.net" To delete an alias omit the part after the equal sign. "A sam=" will delete the sam alias. To get a list of all your aliases send "AL"
<b>F#</b>	Forward message number # to address or callsign following F# (# is 1 to 5) (# is one of the numbered messages returned via the List command).  Example: "F2 youraddr@home.net"
<b>K#</b>	Kill (mark as deleted) message number # (# is one of the numbered messages returned via the List command). Example: "K3"
<b>G#</b>	Return information about closest active RMS Packet Gateway. # is a number indicating how many "close" stations are returned. The default (no #) is 1.
<b>I</b>	Return Information about APRSlink

All informations provided by Winlink.org